

GENERATING SET

- MGB 7000 HML -

FEATURES

- Engine shut down for low oil level (oil alert)
- Large fuel tank - 25l
- Automatic voltage regulation "AVR"
- Sockets: 1x230V 32A 2P+T CEE - 2x230V 16A 2P+T CEE
- Battery 12V (**only for Electric Starter**)
- Circuit breaker
- Silenced
- Meets EC directives for noise and safety



The images are for reference

A.C. GENERATION - 50 Hz

Single-Phase synchronous alternator, self-excited, self-regulated

* Stand-by single-phase power 7.2 kVA (6.5 kW) / 230V / 31.1A

* PRP single-phase power 6 kVA (5.4 kW) / 230V / 26.1A

Cos φ 0.9

Insulation class H

* Output powers according to ISO 8528-1

ENGINE

4-stroke petrol, OHV, Air cooling

Model HONDA GX 390

* Stand-By net power 8.2 kW (11.1 HP)

* PRP net power 6.4 kW (8.7 HP)

Starter Manual recoil Electric Starter

Cylinders/ Displacement 1/ 389 cm³

Speed 3000 rpm

Fuel consumption (75% of PRP) 2.4 l/h

* Output powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity 25 l

Running time (75% of PRP) 10.4 h

IP protection degree IP 23

* Dimensions L x l x h 750x520x660 mm

* Dry weight 93Kg 104 Kg

** Measured acoustic power LWA (pressure LpA) 96 dB(A) (71 dB(A) @ 7m)

** Guaranteed acoustic power LWA (pressure LpA) 96 dB(A) (71 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer / **Acoustic power according to European Directive 2000/14/EC

OPTIONS ON REQUEST

- Earthing kit
- ELCB-GFI (Ground Fault Interruptor) 30mA
- Trolley CTM7/1 (4 ruote D 100 mm)
- Trolley CTM7/3 (2 Folding Handles and 2 wheels)
- Carrying Kit TRM7 (4 Folding Handles)

VERSIONS ON REQUEST

- Sockets version SCHUKO